

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Issued on 11-Oct-2017

· Product identifier

· Trade name: 1000X HY and related products

Valid for the following products:

MICROTHERM® PANEL 1000X HY MICROTHERM® OVERSTICHED 1000X HY MICROTHERM® QUILTED 1000X HY MICROTHERM® FLOPPY 1000X HY

· Details of the supplier of the safety data sheet

 Manufacturer/Supplier: Promat Inc. 1731 Fred Lawson Drive Maryville, TN 37801 Phone: 888-681-0155 Fax: 865-681-0016 E-mail: Sales@promat.us Web site: www.promat.us
 Emergency telephone number: 888-681-0155

· Classification of the substance or mixture

The product is not classified according to the Globally Harmonized System (GHS).

· Label elements

- · GHS label elements Non-Regulated Material
- · Hazard pictograms Non-Regulated Material
- · Signal word Non-Regulated Material
- · Hazard statements Non-Regulated Material
- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *0 Fire = 0 Reactivity



OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Issued on 11-Oct-2017

Trade name: MICROTHERM® 1000X HY and related products

1343-98-2	Silica Fiber		0-12%

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

Hazardous C	Components:	
	Silane, dichlorodimethyl-, reaction product with silica	10-70%
112945-52-5	Amorphous Silica	0-70%
409-21-2	silicon carbide	10-50%
1344-28-1	aluminium oxide	0-25%
	STOT SE 3, H335	
1344-95-2	Silica fiber	0-12%
65997-17-3	Fibrous Glass	0-12%
	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	

· Additional information:

MICROTHERM 1000X HY insulation products contain no respirable fibers (see Section 11) and therefore fall outside the scope of European Community Directive Amendment 97/69/EC.

MICROTHERM 1000X HY insulation products may be supplied encapsulated in covering materials such as woven glass cloth, non-woven polyester cloth, PE foil, aluminum foil and mica sheet.

· Description of first aid measures

· After inhalation: Remove affected person to fresh air. Seek medical attention if symptoms persist.

- · After skin contact:
- Rinse affected areas with water, taking care not to scratch or rub. Seek medical attention if irritation persists. *After eve contact:*
- Flush immediately with copious amounts of water. Do not rub eyes. Seek medical attention if irritation persists.
- After swallowing: In the event of suspected problems, seek medical attention.
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
- No further relevant information available.
- · Extinguishing media
- · Suitable extinguishing agents: Water, carbon dioxide, foam or dry extinguishing media.
- · Special hazards arising from the substance or mixture

Plastic encapsulations used to contain MICROTHERM 1000X HY insulation products will burn if exposed to flames.

- · Advice for firefighters
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

Additional information

MICROTHERM 1000X HY insulation products are classified as "non-combustible" by tests to BS 476 Part 4:1970, Fire Tests on Building Materials and Structures. Non-combustibility test for materials (equivalent to ISO/R 1182).



OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Issued on 11-Oct-2017

Trade name: MICROTHERM[®] 1000X HY and related products

Personal precautions, protective equipment and emergency procedures
 In the event of high dust levels, use approved respiratory protective equipment (see Section 8).
 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up:

Powder and fragments should be cleaned up using a method that will avoid the generation of dust in the workplace atmosphere. The use of a vacuum cleaner fitted with an exhaust air filter fine enough to trap the dust is recommended.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Precautions for safe handling

The handling of MICROTHERM[®] 1000X HY insulation products, especially in the encapsulated form, is unlikely to generate significant quantities of airborne dust. Dust may be generated, however, if MICROTHERM 1000X HY insulation products have to be machined, cut to size, broken up or removed from equipment. In such circumstances, if adequate control of personal exposure cannot be achieved by engineering measures alone, it will be necessary to wear approved respiratory protective equipment with the appropriate nominal protection factor and eye protection.

· Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles:

MICROTHERM® 1000X HY insulation products should be stored in dry conditions.

• Information about storage in one common storage facility: Not required.

- · Further information about storage conditions: None.
- Specific end use(s) No further relevant information available.

· Additional information about design of technical systems: No further data; see section 7.

Components with occupational exposure limits:
 68611-44-9 Silane, dichlorodimethyl-, reaction product with silica
 ACGIH-TLV Short-term value: 3 mg/m³
 Long-term value: 10 mg/m³
 Short-term value: 6 mg/m³
 112945-52-5 Amorphous Silica
 ACGIH-TLV Short-term value: 3 mg/m³
 Long-term value: 4 E mg/m³

OSHA-PEL Short-term value: 5 mg/m³ Long-term value: 4 E mg/m³

(Contd. on page 4)

an etex company



OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Issued on 11-Oct-2017

Trade name: MICROTHERM® 1000X HY and related products

(Contd. from page 3)

409-21-2	silicon carbide	
PEL	Long-term value: 15* 5** mg/m ³ fibrous dust: *total dust **respirable fraction	
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction	
TLV	Long-term value: 10* 3** mg/m ³ fibrous dust:0.1 f/cc; nonfibrous:*inh.,**resp.	
1344-28-	1 aluminium oxide	
PEL	Long-term value: 15*; 15** mg/m ³ *Total dust; ** Respirable fraction	
REL	Long-term value: 10* 5** mg/m ³ as Al*Total dust**Respirable/pyro powd./welding f.	
TLV	Long-term value: 1* mg/m ³ as Al; *as respirable fraction	
1344-95-2 Silica fiber		
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction	
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction	
TLV	Long-term value: 10 mg/m³ synthetic nonfibrous, E	
· Addition	nal information: The lists that were valid during the creation were used as basis.	

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Where sufficient control of exposure to airborne dust cannot be achieved by engineering measures alone, or if irritation problems arise, the following protective equipment may be necessary:

· Breathing equipment:

NIOSH/MSHA or EN approved respiratory protection is recommended for use in airborne concentrations exceeding exposure limits.

Protection of hands:

Protective gloves and protective skin cream



Protective gloves

- · Eye protection: Tightly sealed goggles
- · Body protection: Protective work clothing

an etex company



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Issued on 11-Oct-2017

Page 5

Trade name: MICROTHERM® 1000X HY and related products

9 Physical and chemical properties		
 Information on basic physical and General Information Appearance: 	chemical properties	
• Appearance. Form: Color: • Odor: • Odor threshold:	Solid (may be encapsulated in a covering material) Grey Characteristic Not determined.	
· pH-value:	Not applicable.	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	>1700C (silica) Not determined.	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not determined.	
· Ignition temperature:		
Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not self-igniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits: Lower: Upper:	Not determined. Not determined.	
· Vapor pressure:	Not applicable.	
 Density: Relative density Vapor density Evaporation rate Solubility in / Miscibility with Water: 	0.1-0.5 g/cc Not determined. Not applicable. Not applicable. Not determined.	
· Partition coefficient (n-octanol/wat	ter): Not determined.	
 Viscosity: Dynamic: Kinematic: Other information 	Not applicable. Not applicable. No further relevant information available.	

– an **etex** company



OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Issued on 11-Oct-2017

Page 6

Trade name: MICROTHERM[®] 1000X HY and related products

0 Stability and reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability Product is stable under normal conditions.
- · Thermal decomposition / conditions to be avoided:

COVERING: The organic components applied to the glass cloth, and some coatings and adhesives used with MICROTHERM[®] 1000X HY insulation products could decompose when heated to temperatures greater than 1500 degrees Celsius.

CORE INSULATION: MICROTHERM[®] 1000X HY insulation products are thermally stable up to their recommended maximum operating temperature.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.
- · Additional information:

WHEN HANDLING INSULATION W HICH MAY HAVE BEEN SUBJECTED TO TEMPERATURES IN EXCESS OF THE MAXIMUM RECOMMENDED OPERATING TEMPERATURES CARE MUST BE TAKEN TO ENSURE THAT DUST LEVELS ARE MAINTAINED AS FAR BELOW THE APPROPRIATE CONTROL LIMIT AS IS REASONABLY PRACTICAL.

1 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- Other information (about experimental toxicology):

Note: with filament diameters in the range 6-11 microns, MICROTHERM 1000X HY insulation products contain no respirable fibers as defined by the WHO (World Health Organization).

· Additional toxicological information

The product shows the following dangers according to internally approved calculation methods for preparations:

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

112945-52-5 Amorphous Silica	3
NTP (National Toxicology Program)	
None of the ingredients are listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients are listed.	

Promat Inc. • 1731 Fred Lawson Drive • Maryville • TN • 37801 • P. 865-681-0155 • F. 865-681-0016 • www.promat.us



OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Issued on 11-Oct-2017

Page 7

Trade name: MICROTHERM® 1000X HY and related products

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

Waste treatment methods

· Recommendation:

Waste MICROTHERM 1000X HY insulation products (even after use above their recommended operating temperatures) are not classified as hazardous waste, and may generally be disposed of at a normal landfill site that has been licensed for the disposal of industrial waste.

Where MICROTHERM 1000X HY insulation waste has been contaminated by products that may be classified as hazardous, expert guidance should be sought.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

· UN-Number	
· DOT, ADR, ADN, IMDG, IATA	Non-Regulated Material
· UN proper shipping name	-
· DOT, ADR, ADN, IMDG, IATA	Non-Regulated Material
 Transport hazard class(es) 	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Non-Regulated Material
· Packing group	
· DOT, ADR, IMDG, IATA	Non-Regulated Material
 Environmental hazards: 	
• Marine pollutant:	No
 Special precautions for user 	Not applicable.
 Transport in bulk according to Annex II o 	f
MARPOL73/78 and the IBC Code	Not applicable.
 UN "Model Regulation": 	-



Page 8

Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Issued on 11-Oct-2017

Trade name: MICROTHERM® 1000X HY and related products

•	th and environmental regulations/legislation specific for the substance or mixture	
Sara Section 355	(extremely hazardous substances):	
	ngredients are listed.	
	(Specific toxic chemical listings):	
	luminium oxide	
	Substances Control Act):	
•	Silane, dichlorodimethyl-, reaction product with silica	
	Amorphous Silica	
	silicon carbide	
1344-28-1	aluminium oxide	
1344-95-2	Silicic acid, calcium salt	
65997-17-3	Fibrous Glass	
1343-98-2	Silicic Acid	
	anown to cause reproductive toxicity for females: ngredients are listed.	
	· · ·	
Chemicals k	nown to cause reproductive toxicity for males:	
None of the i	ngredients are listed.	
· Chemicals known to cause developmental toxicity:		
None of the i	ngredients are listed.	
Carcinogeni	c categories	
EPA (Enviro	nmental Protection Agency)	
None of the i	ngredients are listed.	
NIOSH-Ca (National Institute for Occupational Safety and Health)		
This product is listed as a hazardous material under criteria of the Federal OSHA Hazard Communication Standard, 29 CFR 1910.1200		
Standard, 29 GHS label el Hazard picto Signal word	lements Non-Regulated Material ograms Non-Regulated Material Non-Regulated Material cements Non-Regulated Material	

(Contd. Page 9)

an etex company



OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Issued on 11-Oct-2017

an etex company

Trade name: MICROTHERM® 1000X HY and related products

(Contd. from Page 8)

68611-44-9	Silane, dichlorodimethyl-, reaction product with silica	10-70%
112945-52-5	Amorphous Silica	0-70%
409-21-2	silicon carbide	10-50%
10034-76-1	Calcium sulphate	0-25%
1344-28-1	aluminium oxide	0-25%
	STOT SE 3, H335	
1344-95-2	Silicic acid, calcium salt	0-12%
65997-17-3	Fibrous Glass	0-12%
	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision 07/14/2015

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3