

DECLARATION OF PERFORMANCE

Date of issue: 28/01/2019

Replaces: No. 1812-CPR-0121 – CPR – 2018/1 of: 01/04/2018

No. 1812-CPR-0121 – CPR – 2019/1

1	Identification of the product-type: PROMAGLAS EW1	
2	Type and batch numbers: as given on the product label	
3	Intended uses: Fire resisting Glass	
4	Name and contact address of the manufacturer: Etex Building Performance GmbH Scheifenkamp 16 40878 Ratingen Germany Plant: 247 and 247-2	
5	Authorised representative: not applicable.	
6	System or systems of Assessment and Verification of Constancy of Performance (AVCP): system 1 (for resistance to fire).	
7	The construction product is covered by the harmonised standard EN 14449. Notified product certification body: No. 1812 Certificate of Constancy of Performance: 1812-CPD-0121 and 1812-CPD-1109	
8	The construction product is not covered by a European Technical Assessment.	
9	Declared Performance	
	Characteristic	PROMAGLAS EW1-30, 4 / 8 / 4
	Resistance to fire	EW30
	Reaction to fire	NPD
	External fire performances	NPD
	Bullet resistance	NPD
	Explosion resistance	NPD
	Burglar resistance	NPD
	Pendulum body impact resistance	NPD
	Resistance against sudden temperature change and temperature differentials	NPD
	Wind, snow, permanent and imposed load resistance	NPD
	Light transmission [%]	NPD
	Energy transmission g [%]	NPD
	Sound insulation Rw [dB]	NPD
	Heat transfer coefficient U _g [W/m ² K]	NPD

This Declaration of Performance is also valid for glass types derived from the above mentioned by using

- thicker layers of toughened glass
- thicker interlayers (up to 18 mm for EI 30, 22 mm for EI 60, 38 mm for EI 90 and 47 mm for EI 120)
- laminated safety glass instead of toughened glass (same or higher thickness).

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

The reader of this document is invited to verify on the website www.promat-ce.eu the latest version of this DoP.

Information on mounting and fixing is available on request to Promat.

Signed for and on behalf of the manufacturer by:

Name: Tanguy Vanderborght
Function: Managing Director, Etex Building Performance GmbH.

Ratingen, 28th of January, 2019

Signature

