

PROMAT®-READY MIX PRO

Ready-to-use filling compound



Features

- For manual and machine processing (e.g. with airless equipment)
- Tested with Promat® fire protective boards
- Ready for immediate use
- Easy to apply and smooth out
- Long processing time
- Achieves high quality surfaces: Q1 to Q3

Technical data and properties

	PROMAT®-Ready Mix Pro
Reaction to fire	A2, s1-d0
Performance declaration	DoP-20201116-30
Form when delivered	In paste form in the bucket 10 kg, 52 pcs./PAL 20 kg, 32 pcs./PAL
Density	ca. 1600 kg/m ³
Drying time	ca. 24-48 h depending on room temperature, humidity and layer thickness
Surface quality level	Q1-Q3
Indicative consumption	0.25 - 0.9 kg/m ² depending on surface finishing and type of board

This product data sheet is solely intended to provide information on the building material specified above. The information is based on our technical knowledge and experience. Due to the multitude of possible influences when processing and applying our products, it may be a good idea for the processor to carry out their own tests and trials as these only represent general guidelines. No legally binding assurance of specific properties or suitability for a specific purpose can be derived from this. The processor is responsible for always observing any property rights as well as existing laws and regulations themselves. We reserve the right to make all possible or necessary product changes in accordance with national and / or international standards.

Unless otherwise stated, technical data refer to average values from production and are subject to the usual production fluctuations and (where stated) tolerances. If required, the general building inspectorate certificates are available for the products. These must be observed, even if they're not mentioned. The instructions on the products or their packaging as well as the safety data sheets, which can be requested from us, must be observed.

General description

Promat®-Ready Mix PRO ready-to-use filling compound is suitable for manual and mechanical joint filling of Promat® fire protective boards.

Preparation

The surface must be dry, clean and frost-free. Loose particles such as dust must be removed. Make sure that the panels are correctly installed. Depending on the type of Promat® fire protective board, the surface may need to be pre-treated with a commercial primer.

Suitable Promat® fire protective panels

- PROMATECT®-H
- PROMATECT®-100
- PROMATECT®-200
- PROMATECT®-250
- PROMATECT®-L
- PROMATECT®-100X
- PROMATECT®-XS
- PROMAXON®, Type A

The PROMATECT®-L boards must be pre-treated with a commercially available primer.

Processing

- When applied by hand, Promat®-Ready Mix PRO is easy to mix without additional water and can be used directly from the bucket with the trowel/smoothing trowel. When using airless spray equipment, we recommend adding up to max. 1% water for thinning.
- The working temperature must be at least 10°C. Ensure sufficient ventilation.
- Close opened buckets tightly.

Storage requirements

- Store in a cool, frost-free place in a dark and dry location.
- When unopened, the shelf life is 12 months from the date of production.
- Date of manufacture is on the bucket.

For more information visit our website at www.promat.com

Safety information

Please refer to the safety data sheet.