



FSi Promat Paraflam® System

Paraflam® is a perimeter fire stop designed for external facades. Paraflam® is a non-combustible stone wool based product with a foil facing which prevents fibre migration and provides an excellent seal. It is designed to reinstate the fire resistance of a compartment, as well as thermal and acoustic performance

FSi Ltd. products are manufactured to rigid standards of quality. No liability can be accepted for the information provided in this document although it is published in good faith and believed to be correct at time of issue. Any drawings provided are for illustrative purposes only. FSi Ltd. reserves the right to alter product specifications without prior notice, in line with our Company policy of continuous development and improvement. Changes due to new findings are possible, errors and misprints are not excluded. No liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given. FSi Ltd. have no control over the methods of installation, competence of operatives or suitability of site condition. No warranties, expressed or implied, are intended to be given as to the actual performance of the product/system mentioned within this document.

Technical Details

Supporting Test Data: UL-EU-01151-CPR

Test Standard: EN1366-4

Fire Resistance Performance:

Product Depth	Fire Resistance
75mm	EI30
100mm	EI60
120mm	EI120

Void Size

- < 450mm

Installation:

All substrates clean and free from loose of flaking material.

Paraflam® can be supplied in either pre-cut lengths or in sheet form to be cut on site. The size of the cut should accommodate the size of the opening and a minimum compression of 10mm. Where brackets are required Paraflam® must be supported at the correct distances and number of brackets as indicated in the information in this document penetrating the barrier by a minimum of 50% . The steel support brackets are to be mechanically fixed to the substrate with suitable fire resistant anchors. Lengths in excess of 600mm will require minimum 2 brackets. Joints between each length of Paraflam® shall be a straight joint, ensuring a tight fit. Self adhesive foil tape is then applied to each abutting length of Paraflam® to provide a smoke seal and prevent fibre migration.

Issue No.	Drawing Reference	Date
1	PARA-011	28-02-2025

STANDARD DETAIL

Drawing Title:

Paraflam® Cavity Barrier System Installed to Rainscreen Cassette

Scale : NTS

Drawn by : FSi Limited

Reviewed by : N/A

FSi Limited
Westminster Industrial Estate
Tamworth Road
Measham
Leicestershire
DE12 7DS

